

CONTRACT SEALER

Acrylic Emulsion Primer/Sealer



PRODUCT DESCRIPTION

Acrylic emulsion primer/sealer with anti-fungus properties

USES

As a primer/sealer for wall coating materials

AREA OF APPLICATION

Plaster, concrete, brickwork that have strong alkalinity

CHARACTERISTICS

- Excellent adhesion onto substrate.
- Good water resistance.
- Fungus resistance.
- Excellent against alkaline attack on subsequent coats.
- Easy application.

COLOUR AVAILABILITY

White

TECHNICAL DATA

Specific Gravity		1.30 ± 0.05
Drying Time (At 30°C)	Surface Dry	20 minutes
	Hard Dry	1 hour
Shelf Life		Up to 12 months if stored in tightly sealed containers. Keep under roof and in cool place.
Film Thickness	Dry Film (Theoretical)	40 – 60 microns
Solid Content		55 ± 3%
Viscosity		50 ± 15 ps/30°C

SURFACE PREPARATION

Surface shall be dry and free from dirt, dust, oil, grease and foreign matter. Surface unevenness, cracks, etc shall be made good with our cementitious filler.

APPLICATION DATA

No. of Components	: One
No. of Coat	: One
Coverage	: 0.15 – 0.19ltr/m ²
	: 5.25 – 6.65m ² /ltr
Dilution	: 0 – 20% by weight with water
Overcoating Interval	: 2 hours
Method of Application	: By Spray, Brush or Roller

PACKING STYLE

Contract Sealer	20 ltr/can
	5 ltr/can

MATERIAL HANDLING

- * Store materials in cool, well-ventilated and dry place, away from direct sunlight.
- * Ensure adequate ventilated during application.
- * Avoid contact with skin or eyes. Any skin or eye contamination should be washed immediately with plenty of water and seek medical treatment.
- * If swallowed, seek medical advice immediately. Do not induce vomiting.
- * Keep away from heat sources.

Note: The above technical information/ values are given to the best of our knowledge based on laboratories tests, and practical experience. However, due to different applications, site conditions and constraints which are beyond our control, we are not liable for any circumstances due to or relating to the application of usage of our products. We reserve the right to alter or modify any given data without prior notice; therefore it is best to contact us should you have any doubts or enquires.

PS02/2004/15/03 – 09 April 2020