



# SKK HOMES




# SATIN SILK

Ultimate Satin Interior Paint



# SATIN SILK

Ultimate Satin Interior Paint



Sunny  
SS - 68011




Lime  
SS - 68013



Girlie  
SS - 68015



Cool  
SS - 68017




Durian  
SS - 68019



Strong Mint  
SS - 64009



Romance  
SS - 68016



Ocean  
SS - 68007



Morning Sun  
SS - 68008



Avocado ●  
SS - 68018



Lilac  
SS - 68012



Marine Blue ●  
SS - 68014



Luxury ●  
SS - 68020



Lemon ●  
SS - 68004



Classic Brown  
SS - 68002



Cocoa  
SS - 68005

Fengfu Private Ltd WA: +65 - 8363 9464 / +65 - 9816 1980 Email: [fuhuan@ffpte.com](mailto:fuhuan@ffpte.com) / [fenghuan@ffpte.com](mailto:fenghuan@ffpte.com)  
Reg. No.: 202136087D [www.fengfuppte.com](http://www.fengfuppte.com)

● Premium Colours

# The colours on this card are as close to actual paint colours as modern techniques allow.

## Shades of Classic Whites

White

Aloe Vera White  
SS - 60008

Lime White  
SS - 60006

Rose White  
SS - 60001

Orchid White  
SS - 60000

Tender White  
SS - 68009

Vanda White  
SS - 60007

Lily White  
SS - 60009

White Frost  
SS - 68000

Hybrid White  
SS - 60011

Barley White  
SS - 60005





Fengfu Private Ltd WA: +65 - 8363 9464 / +65 - 9816 1980  
Reg. No.: 202136087D www.fengfupte.com

Email: fuhuan@ffpte.com / fenghuan@ffpte.com

# SATIN SILK

## ULTIMATE SHEEN INTERIOR PAINT



Low V.O.C



Washable

### CHARACTERISTICS

- ▶ Fungus resistance
- ▶ It is water-based nature ensure safety and easy application
- ▶ Good water, alkali and chemical resistance
- ▶ Easy maintenance with water and/ or mild detergent
- ▶ Good adhesion onto existing painted surfaces.
- ▶ Environmental friendly
- ▶ Good gloss retention
- ▶ Quick drying
- ▶ Smooth, satin silk gloss finish

### USES

As a high quality decorative and protective finishing coat for interiors, newly primed and old painted surfaces. It is suitable as a topcoat for texture coatings.

### AREA OF APPLICATION

Suitable for primed surfaces of interior concrete, plaster, masonry, PC panel, GRC panel, hard and soft boards, timber etc.

### SURFACE PREPARATION

Surface shall be dry and free from dirt, dust, oil, grease and foreign matter. Surface unevenness, cracks etc. shall be made well with our cementitious filler.

### APPLICATION DATA

Coverage	: 6 to 9m <sup>2</sup> / Liter / Coat (Theoretically)
Dilution	: 0 - 10% by weight with water, if necessary
Over Coating Interval	: 2 hours
Method of Application	: By brush, roll or spray

### MATERIAL HANDLING

Store the materials in a cool and dry place. Keep away from direct sunlight. Ensure adequate ventilated during application. Avoid contact with skin or eyes. Any skin or eye contamination should be washed immediately with plenty of water and seek medical treatment. If swallowed, seek medical advice immediately. Do not induce vomiting. Keep away from heat sources.



032 - 020  
Environmentally Friendly  
Low VOC Paint



CERT NO: 92-2-0074  
SS ISO 9001 : 2000  
Management System Certified