



SKK HOMES




SATIN SILK

Ultimate Satin Interior Paint



SATIN SILK

Ultimate Satin Interior Paint



Sunny
SS - 68011




Lime
SS - 68013




Girlie
SS - 68015



Cool
SS - 68017



Durian
SS - 68019



Strong Mint
SS - 64009



Romance
SS - 68016



Ocean
SS - 68007



Morning Sun
SS - 68008



Avocado ●
SS - 68018



Lilac
SS - 68012



Marine Blue ●
SS - 68014



Luxury ●
SS - 68020



Lemon ●
SS - 68004



Classic Brown
SS - 68002



Cocoa
SS - 68005

● Premium Colours

The colours on this card are as close to actual paint colours as modern techniques allow.

Shades of Classic Whites

White

Aloe Vera White
SS - 60008

Lime White
SS - 60006

Rose White
SS - 60001

Orchid White
SS - 60000

Tender White
SS - 68009

Vanda White
SS - 60007

Lily White
SS - 60009

White Frost
SS - 68000

Hybrid White
SS - 60011

Barley White
SS - 60005





SATIN SILK

ULTIMATE SHEEN INTERIOR PAINT



Low V.O.C



Washable

CHARACTERISTICS

- ▶ Fungus resistance
- ▶ It is water-based nature ensure safety and easy application
- ▶ Good water, alkali and chemical resistance
- ▶ Easy maintenance with water and/ or mild detergent
- ▶ Good adhesion onto existing painted surfaces.
- ▶ Environmental friendly
- ▶ Good gloss retention
- ▶ Quick drying
- ▶ Smooth, satin silk gloss finish

USES

As a high quality decorative and protective finishing coat for interiors, newly primed and old painted surfaces. It is suitable as a topcoat for texture coatings.

AREA OF APPLICATION

Suitable for primed surfaces of interior concrete, plaster, masonry, PC panel, GRC panel, hard and soft boards, timber etc.

SURFACE PREPARATION

Surface shall be dry and free from dirt, dust, oil, grease and foreign matter. Surface unevenness, cracks etc. shall be made well with our cementitious filler.

APPLICATION DATA

Coverage	: 6 to 9m ² / Liter / Coat (Theoretically)
Dilution	: 0 - 10% by weight with water, if necessary
Over Coating Interval	: 2 hours
Method of Application	: By brush, roll or spray

MATERIAL HANDLING

Store the materials in a cool and dry place. Keep away from direct sunlight. Ensure adequate ventilated during application. Avoid contact with skin or eyes. Any skin or eye contamination should be washed immediately with plenty of water and seek medical treatment. If swallowed, seek medical advice immediately. Do not induce vomiting. Keep away from heat sources.



032 - 020
Environmentally Friendly
Low VOC Paint



CERT NO: 92-2-0074
SS ISO 9001 : 2000
Management System Certified